



Vehicle for operation and maintenance of HTF in solar plants with PTC technology.

Technical specifications:

- All the features implemented on the truck are suitable to work with HTF untill 350 °C.
- Thermal oil tank built in carbon steel. Capacity depends on chasis GVM. Incorporates a magnetic level inidcator, thermometer and pressure gauge.
- Thermal insulation of the tank and pipes through microporous material.
- · Pump for working with HTF:
 - · Maximum Flow: 9 m3/h.
 - · Maximum pumping height: 135 m.
- · Electrical resistance to maintain the temperature of the oil tank, in compliance with ATEX regulations.
- Two rear hose support with 25 meters of hose suitable for working with HTF.
- · One additional hose for venting return.
- Vent line with venting cube and valves to control the pressure inside the tank.
- · Access ladder to the tank.
- Control panel for handling the main functions of the vehicle from outside.
- N₂ injection system, consisting of support for bottles of N₂, suitable for blanketing the loop.
- · Side tool boxes and hose carriers.
- · Two rear and side lights.
- · Earth wire and clamps.
- · Identifications plates on valves.
- · Adapted to ATEX regulations.

Optionals:

- Manual hose reels for 25 m hose [1453]
- Hydraulic hose reels for 25 m hose. [1454]
- Thermal oil tank and pipes built in stainless steel. [1452]
- Air Cooler: Placed on the truck, reduces inlet HTF temperature from 400 °C to 105°C. [1402]
- Air Cooler Trailer, reduces inlet HTF temperature from 400 °C to 105°C [1404]
- Additional HTF pump: [1455]
 - Maximum Flow: 6 m3/h.
 - · Maximum pumping height: 20 m.
- Electrical trace to prevent freezing on HTF inside the pipes, valves and pumps. [1456]
- Generator to power the electrical resistance. [1450]
- · Vertical venting tank.
- Labelling. [1156]



Chasis recommended

- Suitable PTO to provide the necessary power to move all the equipment installed.
- Adapted to the gas emission regulations in the country

HTF tank(I)*	Chassis GVW recomended	Traction
4.000	15 Tn	4x2
6.000	18 Tn	4x2

*Final capacity will be limited depending on the GVW of the truck

General conditions

- 1 year warranty
- Operation and mainteinance manual included
- Legalization and registration is not necessary to work on site. If the client requires it, Feniks will provide him with all the necessary information to legalize it.
- Commissioning and training on site is needed for each truck.









